


67791-67720-TIMKEN - 67791-67720-TIMKEN

TAPERED ROLLER BEARINGS

TYPE TS



Bearing Dimensions				Load Ratings							Part Number	
Bore d	O.D. D	Width B		Dynamic ⁽¹⁾ C	Factor ⁽²⁾ Y	Static ⁽³⁾ C ₀	Dynamic ⁽⁴⁾ C ₁₀	Factor ⁽⁵⁾ K	Static ⁽⁶⁾ C ₀	Inner	Outer	
mm	mm	mm		N		N	N		N			
in	in	in		lb		lb	lb		lb			
177.800	267.650	47.625		405000	1.36	105000	76900	1.33	279000	67781	67720	
7.000	10.500	1.875		91100		23800	17100		62500			
Bearing Dimensions												
SHAFT												
Width B		Width C	Eff. C ₂	Max Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Max Housing Fillet Radius r ₁	Backing Shoulder Dia. D ₁	Cage		Geometry Factors		
mm	mm	mm	mm	mm	mm	mm	mm	A ₁ ⁽¹⁾	A ₂ ⁽¹⁾	G ₁	G ₂ C ₃	
47.625	26.700	4.8	16.5	108.0	208.0	3.3	268.0	229.0	4.8	1.8	622.3 122.6 0.1214	
1.875	1.050	0.19	0.65	4.25	8.19	0.13	10.55	9.02	0.19	0.07	8.59 4.84	

Marke	TIMKEN
N° Ean13	3663952326498
Innendurchmesser	177.8 mm
Außendurchmesser	247.65 mm
Dicke	47.625 mm
Verpackung	1

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE