




Rillenkugellager einreihig ZKLN80130-2Z-INA - ZKLN80130-2Z-INA

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/einreihig/zkln80130-2z-ina>

Axial angular contact ball bearings ZKLN80130-2Z
double direction, gap seats on both sides

d	80 mm	Tolerance: -0.008
D	130 mm	Tolerance: -0.015
B	45 mm	Tolerance: -0.25
	60 °	Contact angle
D _{0,max}	120 mm	
d ₁	105 mm	
d _{2,max}	102 mm	
r _{1,max}	0,6 mm	
r _{2,max}	0,6 mm	
m	2,7 kg	Mass
C ₁₀	91000 N	Basic dynamic load rating, axial
C _{0a}	26000 N	Basic static load rating, axial
n _{lim grease}	2700 1/min	Limiting speed for grease lubrication
M _{fr}	1,9 Nm	Bearing frictional torque
G _{ax}	3000 N/mm	Axial rigidity
G _{ti}	3000 Nm/rad	Tilting rigidity
M _r	27,6 kg x cm ²	Mass moment of inertia for rotating inner ring
	3 µm	Axial runout
ZMAR0120		Designation of recommended INA locknut
AM80		Designation of recommended INA locknut
		Locknuts not included in delivery.
M _t	160 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	20604 N	Axial preload force

PRODUKTMERKMALE

Marke	INA
N° Ean13	3663952334981
Innendurchmesser	80 mm
Wasserdichtheit	Deckscheiben auf beiden Seiten
Außendurchmesser	130 mm
Dicke	45 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE