

Kegelrollenlager

EE275105-275158-B-TIMKEN - EE275105-275158-B-TIMKEN

<https://www.123kugellager.ch/kugellager-gehauselager/zyylinderrollenlager/kegelrollenlager/ee275105-275158-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF

| Bearing Dimensions | | | Load Ratings | | | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|------|--|-----------------------------|--------------------------|----------|----------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₀ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | | N | | N | | | | |
| 266.700 | 403.225 | 69.850 | 1070000 | 0.42 | 1.40 | 252000 | 107000 | 1000000 | EE275105 | 275158-B | | |
| 15.5000 | 15.8750 | 1.5000 | 220000 | | | 59000 | 4000 | 350000 | | | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽¹⁾ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft Fillet Radius R ⁽¹⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₁ | C ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| 69.850 | 48.500 | 2.5 | 417.400 | 14.200 | 0.4 | 207.0 | 295.0 | 305.0 | 1451.0 | 201.0 | 0.1505 | | | 28.00 |
| 2.7000 | 1.8125 | 0.10 | 18.4334 | 0.5025 | 0.25 | 11.30 | 11.85 | 15.31 | | | | | | 64.01 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | TIMKEN |
| N° Ean13 | 3663952340593 |
| Innendurchmesser | 266.7 mm |
| Außendurchmesser | 403.23 mm |
| Dicke | 69.85 mm |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE