


Nadelhülsenlager TAM810-IKO - TAM810-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhülsenlager/tam810-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
B	---	---	TAM 810	7.1	---	---	---	---	---	---

Boundary dimensions mm			Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	Shaft dia. H7		Housing bore dia. N7		Max.	Min.	N	N	rpm	---
8	15	10	Max.	Min.	Max.	Min.	Max.	Min.	3 470	2 880	45 000	---

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952351933
Innendurchmesser	8 mm
Außendurchmesser	15 mm
Dicke	10 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE