

Nadelhülsenlager TAM1215-IKO - TAM1215-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/tam1215-iko>

SHELL TYPE NEEDLE ROLLER BEARINGS

Identification number													
Shaft dia. mm	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g			
12	---	---	---	---	---	---	TAM 1215	14	---	---	---		
Boundary dimensions mm			Standard mounting dimensions mm						Basic ratings				
F_w D C f_2			Shaft dia. mm						Basic dynamic load rating C				
Max. Min.			Housing bore dia. mm						Basic static load rating C_0				
Max. Min.			Max. Min.						Allowable rotational speed ^(*) rpm				
12	19	15	1.3	12.000	11.989	19.012	18.991	---	---	7 440	8 320	35 000	IRT 815

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
 Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952352008
Innendurchmesser	12 mm
Außendurchmesser	19 mm
Dicke	15 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE