Nadelhülsenlager
TLAM3018-IKO - TLAM3018-IKO

https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/tlam3018-iko



IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

TAM TLAM

Shaft dia. mm	Identification number: Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
30	—	—					TLAM 3018	40	—	—

Boundary dimensions mm F_w	D	C	t_2 Max.	Standard mounting dimensions mm: Shaft dia. h6 Max.	Shaft dia. h6 Min.	Housing bore dia. J7 Max.	Housing bore dia. J7 Min.	Housing bore dia. N7 Max.	Housing bore dia. N7 Min.	Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed(1) rpm	Assembled inner ring
30	37	18	2.8	30.000	29.987	—	—	36.992	36.967	16 400	29 800	12 000	—

Note(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

123BEARING

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952355115
Innendurchmesser	30 mm
Außendurchmesser	37 mm
Dicke	18 mm
Verpackung	1

kontakt@123kugellager.ch
+49 (0) 800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE