


Nadelhülsenlager YB910-IKO - YB910-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/yb910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	—	—	YB 910 12.7	
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed(*)		Assembled inner ring
F_w	D	C	Shaft dia. h8	Housing bore dia. J7	N	C_0	N	rpm	—	
14.288 ($\frac{9}{16}$)	19.050 ($\frac{3}{4}$)	15.881 (.625)	14.288 Max.	14.277 Min.	19.062 Max.	19.041 Min.	14 300	26 700	11 000	—

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952361611
Innendurchmesser	14.288 mm
Innendurchmesser	9/16" inch
Außendurchmesser	19.05 mm
Außendurchmesser	3/4" inch
Dicke	15.88 mm
Dicke	5/8" inch
Gewicht	22 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE