


# Nadelhülsenlager BHAM1212-IKO - BHAM1212-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bham1212-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																																																						
	Standard	Mass (Ref.) g	Closed end																																																																
19.050 ( $\frac{3}{8}$ )	—	—	—	—	—	—	—	—	—	—	—	—	—																																																						
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="2">mm(inch)</th> <th colspan="4">Standard mounting dimensions</th> <th colspan="2">mm</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="2">Allowable rotational speed<sup>(1)</sup></th> <th colspan="2">Assembled inner ring</th> </tr> <tr> <th><math>F_w</math></th> <th><math>D</math></th> <th><math>C</math></th> <th><math>F_w</math></th> <th>Shaft dia. h6</th> <th>Housing bore dia. J7</th> <th>Max.</th> <th>Min.</th> <th>Max.</th> <th>Min.</th> <th>C</th> <th>C<sub>0</sub></th> <th>C<sub>0</sub></th> <th>N</th> <th>N</th> <th>rpm</th> <th colspan="2">IRB 812-1</th> </tr> </thead> <tbody> <tr> <td>19.050 (<math>\frac{3}{8}</math>)</td> <td>26.988 (<math>1\frac{1}{8}</math>)</td> <td>19.051 (<math>\frac{750}{39}</math>)</td> <td>1.3</td> <td>19.050</td> <td>19.037</td> <td>27.000</td> <td>26.979</td> <td>16 600</td> <td>22 600</td> <td>20 000</td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> </tr> </tbody> </table>														Boundary dimensions			mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>		Assembled inner ring		$F_w$	$D$	$C$	$F_w$	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	Max.	Min.	C	C <sub>0</sub>	C <sub>0</sub>	N	N	rpm	IRB 812-1		19.050 ( $\frac{3}{8}$ )	26.988 ( $1\frac{1}{8}$ )	19.051 ( $\frac{750}{39}$ )	1.3	19.050	19.037	27.000	26.979	16 600	22 600	20 000						
Boundary dimensions			mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>		Assembled inner ring																																																		
$F_w$	$D$	$C$	$F_w$	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	Max.	Min.	C	C <sub>0</sub>	C <sub>0</sub>	N	N	rpm	IRB 812-1																																																			
19.050 ( $\frac{3}{8}$ )	26.988 ( $1\frac{1}{8}$ )	19.051 ( $\frac{750}{39}$ )	1.3	19.050	19.037	27.000	26.979	16 600	22 600	20 000																																																									

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952361819
Innendurchmesser	19.05 mm
Außendurchmesser	26.988 mm
Dicke	19.05 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE