


# Nadelhülsenlager YB124-IKO - YB124-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/yb124-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
19.050 ( $\frac{3}{4}$ )	—	—	—	—	—	—	—	—	YB 124 8.5		
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm			
$F_w$	$D$	$C$	$\frac{D}{2}$	Shaft dia. $h_6$	Housing bore dia. $J_7$	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring		
19.050	25.400	6.35	250	19.050 Max.	19.037 Min.	25.412 Max.	25.391 Min.	7 820 N	10 200 N	8 000 rpm	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952361826
Innendurchmesser	19.05 mm
Außendurchmesser	25.4 mm
Dicke	6.35 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE