


Nadelhülsenlager BHAM1412-IKO - BHAM1412-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bham1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g																																																	
	Standard	Mass (Ref.) g	Closed end																																																											
22.225 (7/8)	---	---	---	---	---	---	---	---	---	---	---	---	---																																																	
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="1">Allowable rotational speed⁽¹⁾</th> <th colspan="1">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th colspan="2">Shaft dia. h6</th> <th colspan="2">Housing bore dia. J7</th> <th>C</th> <th>C_0</th> <th>C_0</th> <th>rpm</th> <th></th> </tr> <tr> <td></td> <td></td> <td></td> <td>Max.</td> <td>Min.</td> <td>Max.</td> <td>Min.</td> <td>N</td> <td>N</td> <td>N</td> <td></td> <td></td> </tr> </thead> <tbody> <tr> <td>22.225</td> <td>30.162</td> <td>19.05</td> <td>22.225</td> <td>22.212</td> <td>30.176</td> <td>30.151</td> <td>18 000</td> <td>26 100</td> <td>18 000</td> <td></td> <td>IRB 1012</td> </tr> </tbody> </table>														Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring	F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	rpm					Max.	Min.	Max.	Min.	N	N	N			22.225	30.162	19.05	22.225	22.212	30.176	30.151	18 000	26 100	18 000		IRB 1012
Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	Assembled inner ring																																																		
F_w	D	C	Shaft dia. h6		Housing bore dia. J7		C	C_0	C_0	rpm																																																				
			Max.	Min.	Max.	Min.	N	N	N																																																					
22.225	30.162	19.05	22.225	22.212	30.176	30.151	18 000	26 100	18 000		IRB 1012																																																			

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952361871
Innendurchmesser	22.225 mm
Außendurchmesser	30.162 mm
Dicke	19.05 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE