

Nadelhülsenlager YB1412-IKO - YB1412-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/yb1412-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
22.225 ($\frac{7}{8}$)	—	—	—	—	—	—	—	—	YB 1412 31		
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	$\frac{h_6}{2}$	Shaft dia. h_6	Housing bore dia. J_7	C	C_0	N	N	rpm	IRB 1012
22.225	28.575	19.05	—	22.225 Max.	22.212 Min.	28.587 Max.	28.566 Min.	26 300	50 700	7 000	IRB 1012

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3616060457448
Innendurchmesser	22.225 mm
Außendurchmesser	28.587 mm
Dicke	19.05 mm
Gewicht	31 g
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE