


Nadelhülsenlager BHAM1616-IKO - BHAM1616-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/bham1616-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Standard			Closed end			Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
25.400 (1)	—	—	—	—	—	—	—	BHAM 1616	48	—	—	—	
Boundary dimensions mm(inch) Standard mounting dimensions mm													
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>t</i>	Shaft dia. h _s	Housing bore dia. J7					N	N		
25.400	33.338	25.40(1.000)	3.4	25.400 25.387	33.352 33.327					26 400	44 500	15 000	
<small>Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable. Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.</small>													

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952362038
Innendurchmesser	25.4 mm
Außendurchmesser	33.338 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE