


## Nadelhülsenlager YB1612-IKO - YB1612-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/nadelhulsenlager/yb1612-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
25.400 (1)	—	—	—	—	—	—	—	—	—	—	—	YB 1612	34.5
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C <sub>d</sub>	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring				
F <sub>w</sub>	D	C	Shaft dia. h6 Max.   Min.	Housing bore dia. J7 Max.   Min.	C								
25.400	31.750	19.05	25.400   25.387	31.764   31.739	28 200	58 000	6 000	IRB 1212					

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952362052
Innendurchmesser	25.4 mm
Innendurchmesser	1" inch
Außendurchmesser	31.75 mm
Außendurchmesser	1 1/4" inch
Dicke	19.05 mm
Dicke	3/4" inch
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE