


Nadellager GBRI122416-IKO - GBRI122416-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbri122416-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
19.050 (3/4)	GBRI 122416	150	19.050 ₀ ^{+0.005}	38.100 ₀ ^{+0.005}	25.400 ₀ ^{+0.005}	25.650	25.400 ₀ ^{+0.005}

Standard mounting dimensions mm		Basic dynamic load rating C ₀ N	Static load rating C ₀ N	Allowable rotational speed (P) rpm	Assembled inner ring LRBZ 121616		
d ₄ Min.	d ₄ Max.						
24	24.4	33.3	0.6	41 400	67 100	6 000	LRBZ 121616

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377421
Innendurchmesser	19.05 mm
Außendurchmesser	38.1 mm
Dicke	25.65 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE