


Nadellager GBR223016-IKO - GBR223016-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbr223016-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (¹⁾)	
			F _o	D	C	D _s Max.	r _{as} max
34.925 (1 3/8)	GBR 223016	137	34.925(¹ / ₂)	47.625(1 7/8)	25.400(1)	42.8	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(²⁾)					
N	N	rpm					
49 500	91 800	4 500					

Notes:
¹⁾ Maximum permissible corner radius of the housing.
²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
 Remarks:
 1. The outer ring has an oil groove and an oil hole.
 2. No grease is pre-packed. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377773
Innendurchmesser	34.925 mm
Außendurchmesser	47.625 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE