


Nadellager GBR243320-IKO - GBR243320-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbr243320-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F _d	D	C	D _s Max.	r _{as max}
38.100 (1 1/2)	GBR 243320	205	38.100 (1 1/2)	52.388 (2 1/2)	31.750 (1 1/2)	47.3	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
64 100	121 000	4 000					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377797
Innendurchmesser	38.1 mm
Außendurchmesser	52.388 mm
Dicke	31.75 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE