


Nadellager GBR263516-IKO - GBR263516-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbr263516-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾)	
			F _o	D	C	D _s Max.	r _{as} max
41.275 (1 5/8)	GBR 263516	180	41.276 (1.625)	55.562 (2 1/8)	25.400 (1)	50.5	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
56 600	105 000	3 500					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377803
Innendurchmesser	41.275 mm
Außendurchmesser	55.562 mm
Dicke	25.4 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE