


## Nadellager GBR1284828-IKO - GBR1284828-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbri284828-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
<b>44.450</b> (1 1/2)	<b>GBR1 284828</b>	925	44.450 (1) 0	76.200 (3) 0	44.450 (1) 0	44.700	57.150 (2) 0

Standard mounting dimensions mm		Basic dynamic load rating $C_0$	Limiting load rating $C_0$	Allowable rotational speed (1) rpm	Assembled inner ring		
$d_a$	$D_a$						
Min.	Max.	$r_{as max}$ (1)	N	N			
52.5	55	69.2	1.5	133 000	276 000	2 500	<b>LRBZ 283628</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952377889
Innendurchmesser	44.45 mm
Außendurchmesser	76.2 mm
Dicke	44.45 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE