

## Nadellager BRI61816-UU-IKO - BRI61816-UU-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/bri61816-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>9.525</b> ( $\frac{3}{8}$ )	<b>BRI 61816 UU</b>		<b>78</b>	9.525 ( $\frac{3}{8}$ )	28.575 (1 $\frac{1}{8}$ )	25.400 (1 )	25.650
$F_w$	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Min.	Max.				Min.	Max.
	14	24.5	18 300	20 000	12 000	<b>LRBZ 61016 B</b>	

Notes: (\*) Minimum allowable value of chamfer dimension r  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382463
Innendurchmesser	9.525 mm
Innendurchmesser	3/8" inch
Außendurchmesser	28.575 mm
Außendurchmesser	1 1/8" inch
Dicke	25.4 mm
Dicke	1" inch
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE