


## Nadellager BRI162820-U-IKO - BRI162820-U-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/bri162820-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>25.400</b> (1)		<b>BRI 162820 U</b>	196	25.400 (1)	44.450 (1 3/4)	31.750 (1 1/4)	32.000	
F <sub>w</sub>	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring		
	Min.	Max.				Min.	Max.	
31.750 (1 1/4)	30.5	30.7	39.2	0.6	36 000	53 500	6 500	<b>LRBZ 162020 B</b>

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382562
Innendurchmesser	25.4 mm
Innendurchmesser	1" inch
Außendurchmesser	44.45 mm
Außendurchmesser	1 3/4" inch
Dicke	31.75 mm
Dicke	1 1/4" inch
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE