


Nadellager BRI365628-UU-IKO - BRI365628-UU-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/bri365628-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | |
|----------------------------|-----------------------------------|---|-------------------------------------|--|--|-----------------------|---------------|
| | With two seals | With one seal | | d | D | C | B |
| 57.150 (2 1/4) | BRI 365628 UU | | 980 | 57.150 (2 1/4) | 88.900 (3 1/2) | 44.450 (1 3/4) | 44.700 |
| F_w | Standard mounting dimensions (mm) | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | |
| | Min. d_s | Max. D_s Max. r as max. ⁽¹⁾ | | | | | |
| 69.850 (2 3/4) | 65 | 67 80.7 | 98 700 | 189 000 | 2 500 | LRBZ 364428 B | |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952382746 |
| Innendurchmesser | 57.15 mm |
| Außendurchmesser | 88.9 mm |
| Dicke | 44.45 mm |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE