


Nadellager BRI406028-UU-IKO - BRI406028-UU-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/bri406028-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------------------|---------------|-------------------------------------|--|--|-----------------------|---------------|----------------------|
| | With two seals | With one seal | | d | D | C | B | |
| 63.500 (2 1/2) | BRI 406028 UU | | 1 065 | 63.500 (2 1/2) | 95.250 (3 3/4) | 44.450 (1 3/4) | 44.700 | |
| F_w | Standard mounting dimensions (mm) | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | | |
| | Min. | Max. | | | | d_s | D_s as max | |
| 76.200 (3) | 71 | 73 | 87.0 | 1.5 | 105 000 | 211 000 | 2 500 | LRBZ 404828 B |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952382777 |
| Innendurchmesser | 63.5 mm |
| Außendurchmesser | 95.25 mm |
| Dicke | 44.45 mm |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE