


Nadellager

GBR243320-UU-IKO - GBR243320-UU-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbr243320-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		F_w	D	C
38.100 (1.5)	GBR 243320 UU		200	38.100(1.5)	52.388(2.06)	31.750(1.25)
Standard mounting dimensions mm		Ball dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_s	r as max	N	N	rpm		
47.3	0.6	54 200	97 700	2 000		

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952382999
Innendurchmesser	38.1 mm
Außendurchmesser	52.388 mm
Dicke	31.75 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE