

# Nadellager

## GBR263520-UU-IKO - GBR263520-UU-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbr263520-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>41.275</b> (1 5/8)	<b>GBR 263520 UU</b>		215	41.275 (1 7/8)	55.562 (2 1/8)	31.750 (1 1/2)
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball dynamic load rating $C_0$	Allowable rotational speed(*)		
$D_A$ Max.	$r$ as max (°)	N	N	rpm		
50.5	0.6	56 600	105 000	1 900		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(°) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952383002
Innendurchmesser	41.275 mm
Außendurchmesser	55.562 mm
Dicke	31.75 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE