

Nadellager

GBR445628-UU-IKO - GBR445628-UU-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbr445628-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		F_w	D	C
69.850 (2 3/4)	GBR 445628 UU		610	69.850 ± 0.015	88.900 ± 0.015	44.450 ± 0.015
Standard mounting dimensions mm		Seal dynamic load rating C	Ball dynamic load rating C_0	Allowable rotational speed ^(*)		
D_A Max.	r as max (°)	N	N	rpm		
82	1.5	97 200	197 000	1 100		

Notes: (*) Minimum allowable value of chamfer dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952383132
Innendurchmesser	69.85 mm
Außendurchmesser	88.9 mm
Dicke	44.45 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE