


Nadellager GBR1284828-UU-IKO - GBR1284828-UU-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/gbri284828-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | | |
|----------------------------|-----------------------|-----------------------------------|---------------------|------------------------------|-------------------------------------|---|--|----------------------|------------------------------------|
| | With two seals | With one seal | | d | D | C | | | |
| 44.450 (1 3/4) | GBR1 284828 UU | | 960 | 44.450 (1 3/4) | 76.200 (3) | 44.450 (1 3/4) | | | |
| B | F _w | Standard mounting dimensions - mm | | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring | |
| | | Min. | Max. | D _s Max. | | | | | r _{as max} ⁽¹⁾ |
| 44.700 | 57.150 (2 1/4) | 52.5 | 55 | 69.2 | 1.5 | 87 500 | 161 000 | 1 400 | LRBZ 283628 |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952383514 |
| Innendurchmesser | 44.45 mm |
| Innendurchmesser | 1 3/4" inch |
| Außendurchmesser | 76.2 mm |
| Außendurchmesser | 3" inch |
| Dicke | 44.45 mm |
| Dicke | 1 3/4" inch |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE