


Nadellager
NAS5034-UU-NR-IKO - NAS5034-UU-NR-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/nas5034-uu-nr-iko>



ROLLER BEARINGS

Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (kg)	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
170	NAS 5034UU	NR	22.5	170	260	270	122	121	99	11

f	c	r _s mm	J	Basic dynamic load rating C	Static load rating C ₀	Allowable rotational speed ^(*)
				N	N	rpm
4	3.5	1.5	204.5	857 000	1 730 000	800

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAS and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952387109
Innendurchmesser	170 mm
Außendurchmesser	260 mm
Dicke	122 mm
Verpackung	1

kontakt@123kugellager.ch
+49 (0) 800 001 076 6
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE