

Nadellager NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/nax6040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number											
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g		
60					NAX 6040Z	454	---	---	---		
Boundary dimensions mm											
F_w	D	D_1	D_2	L	H	r_1 min.	d_f	Basic rating group d_a Min. mm	Basic dynamic load rating C Radial Axial	Basic static load rating C_0 Radial Axial	Allowable rotational speed ⁽²⁾ rpm
60	72	85	86.5	40	17	12	1	60	75 47 500 41 400	103 000 89 700	4 000

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390376
Innendurchmesser	60 mm
Außendurchmesser	72 mm
Dicke	40 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE