

Nadellager NAX7040Z-IKO - NAX7040Z-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/nax7040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Shaft dia. mm	Identification number					
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g
70		NAX 7040Z	606			

Boundary dimensions mm										Basic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	
F _w	D	D ₁	D ₂	L	H	r _s min.	d _i	Radial	Axial		Radial	Axial		
70	85	95	96.5	40	18	11	1	70	85	55 500	43 100	120 000	101 000	3 500

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390550
Innendurchmesser	70 mm
Außendurchmesser	85 mm
Dicke	40 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE