

# Nadellager NAXI1730-IKO - NAXI1730-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/naxi1730-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g			
17	<b>NAXI 1730</b>	99	—	—	—	—	—	—	17	30	35

  

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring			
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sub>max</sub>	r <sub>min</sub>	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>		Radial	Axial			Radial	Axial	
36	30	20.5	10	10.5	0.3	0.3	20	20	29	19	17	600	14 200	25 400	19 700	7 500	<b>LRT 172020</b>

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
 Remark 1: The outer ring has an oil groove and an oil hole.  
 2: Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390765
Innendurchmesser	17 mm
Außendurchmesser	30 mm
Dicke	30 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE