

Nadellager NAXI1730Z-IKO - NAXI1730Z-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/naxi1730z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
17		NAXI 1730Z	103	—	—	—	17	30	35

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
D ₂	L	B	H		Radial	Axial			Radial
36	30	20.5	10	17 600	14 200	25 400	19 700	7 500	LRT 172020

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390772
Innendurchmesser	17 mm
Außendurchmesser	30 mm
Dicke	30 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE