

# Nadellager NBXI1730-IKO - NBXI1730-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/nbxi1730-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
17	---	---	NBXI 1730			108	17	30	35

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sup>(1)</sup>	r <sub>max</sub>	r <sub>min</sub>	d <sub>4</sub>	d <sub>5</sub>		Radial	Axial			Radial
36	30	20.5	10	10.5	0.3	0.3	20	33	19	17 600	19 000	25 400	48 700	11 000	LRT 172020

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390789
Innendurchmesser	17 mm
Außendurchmesser	30 mm
Dicke	30 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE