

Nadellager NBXI1730Z-IKO - NBXI1730Z-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/nbxi1730z-iko>

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing

With Inner Ring

Needle Roller Bearings with Thrust Roller Bearing

With Inner Ring

NBX1-Z

Identification number

Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d	D	D ₁
17	---	---	---	---	---	---	17	30	35

NBX1 1730Z

111

17

30

35

Boundary dimensions mm										Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾		Assembled inner ring
D ₂	L	B	H	I ₁	(¹) r _{max}	(²) r _{min}	d ₁	d ₂	d ₃	Radial	Axial	Radial	Axial	rpm	rpm	
36	30	20.5	10	10.5	0.3	0.3	20	33	19	17	600	19 000	25 400	48 700	11 000	LRT 172020

Notes:
(¹) Minimum allowable value of chamfer dimension r.
(²) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remark 1: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390796
Innendurchmesser	17 mm
Außendurchmesser	30 mm
Dicke	30 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE