

Nadellager NAXI3532-IKO - NAXI3532-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/naxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i							
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover										
35	NAXI 3532	265	—	—	—	—	35	52	60							
Boundary dimensions mm																
D ₂	L	B	H	I ₁	r ⁽¹⁾	r _{max} ⁽²⁾	r _{min} ⁽²⁾	d ₄	d ₅	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾	Assembled inner ring			
61	32	20	13	10	0.6	0.3	40	40	52	39	29 400	26 900	54 100	50 000	5 500	LRT 354020

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remark 1: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952390925
Innendurchmesser	35 mm
Außendurchmesser	52 mm
Dicke	32 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE