

# Nadellager NAXI5040-IKO - NAXI5040-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/naxi5040-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number																	
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g	d	D	D <sub>i</sub>					
	50	NAXI 5040	582	—	—	—	—	—									
Boundary dimensions mm																	
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sup>(1)</sup>	r <sub>max</sub>	r <sub>min</sub>	d <sub>4</sub>	d <sub>5</sub>	Radial	Axial	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>	Assembled inner ring		
86.5	40	25.5	17	12	1	1	60	60	75	59	47	500	41 400	103 000	89 700	4 000	LRT 506025

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952391045
Innendurchmesser	50 mm
Außendurchmesser	72 mm
Dicke	40 mm
Verpackung	1

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE