

Nadellager NBXI5040Z-IKO - NBXI5040Z-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/nadellager/radial/nbxi5040z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number

Shaft dia. mm	Mass (Ref.) g		Mass (Ref.) g		Mass (Ref.) g		d	D	D ₁
	With dust cover	Without dust cover	With dust cover	Without dust cover	With dust cover	Without dust cover			
50	---	---	---	---	---	---	50	72	85

NBXI 5040Z 703

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring						
D ₂	L	B	H			Radial	Axial			Radial	Axial				
86.5	40	25.5	17	12	1	1	60	82	59	47 500	64 600	103 000	224 000	4 000	LRT 506025

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUKTMERKMALE

Marke	IKO
N° Ean13	3663952391076
Innendurchmesser	50 mm
Außendurchmesser	72 mm
Dicke	40 mm
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE