


Gelenklager GE SB75A-IKO - SB75A-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/sb75a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | Mass (Ref.) kg | Boundary dimensions mm | | | | | Permissible tilting angle degree | |
|---------------------------|-----------------------|---|--|----------------|----|----|-------------------------------|--|---|
| | | | d | D | B | C | d _k ⁽¹⁾ | | |
| 75 | SB 75A | 3.02 | 75 | 120 | 64 | 55 | 110 | 0.6 | 5 |
| Mounting dimensions mm | | Dynamic load capacity C _d N | Static load capacity C _s N | | | | | | |
| d _s | D _s | | C _d | C _s | | | | | |
| Min. Max. ⁽²⁾ | Max. Min. | N | N | | | | | | |
| 79.5 89.5 | 115.5 102 | 593 000 | 3 560 000 | | | | | | |

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952391427 |
| Innendurchmesser | 75 mm |
| Außendurchmesser | 120 mm |
| Dicke | 64 mm |
| Typ | GE |
| Schmierung | ohne |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE