


Gelenklager GE GE240ES-IKO - GE240ES-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/ge240es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | Permissible tilting angle degree | | |
|---------------------------|-----------------------|----------------|---|--|------------|-----|-----|----------------|--------------------|--|---|----------------|
| | Without seals | With seals | | d | D | B | C | d _s | r ₁ (1) | r ₂ (1) | α | α ₁ |
| 240 | GE 240ES | | 40,4 | 240 | 340 | 140 | 100 | 300 | 1,1 | 1,1 | 8 | 6 |
| Mounting dimensions mm | | | Dynamic load capacity C _d N | Static load capacity C _s N | | | | | | | | |
| d _s | | D _s | | | | | | | | | | |
| Min. | Max.(2) | Max. | Min. | | | | | | | | | |
| 247 | 265 | 333 | 296 | 2 940 000 | 17 700 000 | | | | | | | |

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952392110 |
| Innendurchmesser | 240 mm |
| Außendurchmesser | 340 mm |
| Dicke | 140 mm |
| Typ | GE |
| Schmierung | ohne |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE