


Gelenklager GE GE260ES-IKO - GE260ES-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/ge/ge260es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | Permissible tilting angle degree | | |
|---------------------------|-----------------------|-----------------------------------|----------------------|----------------------------------|-----|------------|-----|-------|-----------|--|----------|------------|
| | Without seals | With seals | | d | D | B | C | d_s | r_1 (1) | r_2 (1) | α | α_1 |
| 260 | GE 260ES | | 52.0 | 260 | 370 | 150 | 110 | 325 | 1.1 | 1.1 | 7 | 6 |
| Mounting dimensions mm | | Dynamic load capacity C_d | | Static load capacity C_s | | | | | | | | |
| d_s | | D_s | | N | | N | | | | | | |
| Min. | Max.(2) | Max. | Min. | | | | | | | | | |
| 267 | 288 | 363 | 320 | 3 510 000 | | 21 000 000 | | | | | | |

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | IKO |
| N° Ean13 | 3663952392127 |
| Innendurchmesser | 260 mm |
| Innendurchmesser | 10.236" inch |
| Außendurchmesser | 370 mm |
| Außendurchmesser | 14.567" inch |
| Dicke | 150 mm |
| Dicke | 5.906" inch |
| Typ | GE |
| Schmierung | ohne |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE