


## Kurvenrollen CF30-UUR-IKO - CF30-UUR-IKO

<https://www.123kugellager.ch/kugellager-gehauselager/rillenkugellager/kurvenrollen/cf30-uur-iko>



### CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UUR

| Stud dia.<br>mm | Identification number   |                             |                         |                             |                         |                             |                         |                             | Mass (Ref.) |    |    |                |         |
|-----------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----------------|---------|
|                 | Shield type             |                             |                         |                             | Sealed type             |                             |                         |                             | g           | D  | C  | d <sub>1</sub> | G       |
|                 | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring |             |    |    |                |         |
| <b>30</b>       | <b>CF 30 UUR</b>        |                             |                         |                             |                         |                             |                         |                             | 1 870       | 80 | 35 | 30             | M30×1.5 |

| Boundary dimensions mm |    |                |                |                |                |                |                |                  |     |                  | Mounting dimension<br>f<br>Min.<br>mm | Maximum<br>ignoring<br>stress<br>N·m | Ball dynamic<br>load rating<br>C | Ball static<br>load rating<br>C <sub>0</sub> | Maximum<br>allowable<br>static load<br>N |
|------------------------|----|----------------|----------------|----------------|----------------|----------------|----------------|------------------|-----|------------------|---------------------------------------|--------------------------------------|----------------------------------|--|--|
| G <sub>1</sub>         | B  | B <sub>1</sub> | B <sub>2</sub> | B <sub>3</sub> | C <sub>1</sub> | g <sub>1</sub> | g <sub>2</sub> | r <sub>max</sub> | (°) | r <sub>max</sub> |                                       |                                      |                                  |  |  |
| 32                     | 37 | max            | 100            | max            | 63             | 15             | 1              | 8                | 4   | 1                | 49                                    | 438                                  | 45 400                           | 85 100                                       | 85 100                                   |

## PRODUKTMERKMALE

|                  |               |
|------------------|---------------|
| Marke            | IKO           |
| N° Ean13         | 3663952441580 |
| Innendurchmesser | 30 mm         |
| Außendurchmesser | 80 mm         |
| Dicke            | 35 mm         |
| Verpackung       | 1             |

[kontakt@123kugellager.ch](mailto:kontakt@123kugellager.ch)

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE