

Gelenkköpfe SI SIL6-T-K-DURBAL - SIL6-T-K-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/si/sil6-t-k-durbal>

SIL6-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | | measurement [mm] | | | | | | |
|-------------------|------------------|------------------|-----|---|----------------|----------------|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
| | SIL 6 T/K | 6 | M 6 | 9 | 6,75 | 20 | 10,0 | 13 |

| type | measurement [mm] | | | load rating C ₀ [N] | weight [kg] |
|----------------|--------------------|----|----|--------------------------------------|----------------|
| | l ₃ min | W | h | | |
| SI / SIL 6 T/K | 12 | 11 | 30 | 7,7 | 0,022 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952489117 |
| Innendurchmesser | 6 mm |
| Innendurchmesser | 0.236" inch |
| Außendurchmesser | 20 mm |
| Außendurchmesser | 0.787" inch |
| Dicke | 9 mm |
| Dicke | 0.354" inch |
| Typ | SI |
| Gewicht | 22 g |
| Gewinde | Linksgewinde |
| Schmierung | ohne |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE