

Gelenkköpfe SI

SIL20-T-K-DURBAL - SIL20-T-K-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/si/sil20-t-k-durbal>

SIL20-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

| order number | right hand thread | left hand thread | measurement [mm] | | | | | | |
|--------------|-------------------|------------------|------------------|------------|----|----------------|----------------|----------------|----------------|
| SIL 20 T/K | | | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
| | | | 20 | M 20 x 1,5 | 25 | 18,00 | 50 | 27,5 | 34 |

| type | measurement [mm] | | | load rating C ₁₀ [N] | weight [kg] |
|-----------------|--------------------|----|----|---------------------------------------|----------------|
| | l ₃ min | W | h | | |
| SI / SIL 20 T/K | 33 | 30 | 77 | 14 | 57,0 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952489568 |
| Innendurchmesser | 20 mm |
| Außendurchmesser | 50 mm |
| Dicke | 25 mm |
| Typ | SI |
| Gewicht | 420 g |
| Gewinde | Linksgewinde |
| Schmierung | ohne |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE