

Winkelgelenke SA SAL8-E-DURBAL - SAL8-E-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/sal8-e-durbal>

SAL8-E



male thread: lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication is necessary

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
SAL 8 E		8	M 8	8	6,0	24	

type	measurement [mm]				n [°]	load rating C ₀ [N]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 8 E	22	14	42	15	12,9	0,029	

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952497907
Innendurchmesser	8 mm
Außendurchmesser	24 mm
Dicke	8 mm
Typ	SA
Gewicht	29 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE