

Winkelgelenke SA SAL15-ES-DURBAL - SAL15-ES-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/sal15-es-durbal>

SAL15-ES



male thread: lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication is necessary

| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| | SAL 15 ES | 15 | M 14 | 12 | 10,0 | 40 |

| type | measurement [mm] | | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----------------|----|---|-------|---------------------------------|-------------|
| | l ₁ min | l ₂ | h | | | | |
| SA / SAL 15 ES | 34 | 20 | 63 | 8 | 8 | 36,0 | 0,140 |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952498072 |
| Innendurchmesser | 15 mm |
| Außendurchmesser | 40 mm |
| Dicke | 12 mm |
| Typ | SA |
| Gewicht | 140 g |
| Gewinde | Linksgewinde |
| Schmierung | mit |
| Verpackung | - |
| Standard | Ohne Standard |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE