

Winkelgelenke SA SAL25-ES-2RS-DURBAL - SAL25-ES-2RS-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/sal25-es-2rs-durbal>

SAL25-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 25 ES (-2RS)	25	M 24 x 2	20	17,0	64	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 25 ES (-2RS)	53	32	94	7	83,0	0,560	

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952498270
Innendurchmesser	25 mm
Außendurchmesser	64 mm
Dicke	20 mm
Typ	SA
Gewicht	560 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE