

Winkelgelenke SA SAL60-ES-DURBAL - DSAL60-ES-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/dsal60-es-durbal>

SAL60-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



| order number | | measurement [mm] | | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|--|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | |
| | SAL 60 ES | 60 | M 52 x 3 | 44 | 38,0 | 135 | |

| type | measurement [mm] | | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----------------|-----|---|----------|---------------------------------------|----------------|
| | l ₁ min | l ₂ | h | | | | |
| SA / SAL 60 ES | 115 | 60 | 210 | 6 | 450,0 | 5,900 | |

PRODUKTMERKMALE

| | |
|------------------|---------------|
| Marke | DURBAL |
| N° Ean13 | 3663952498751 |
| Innendurchmesser | 60 mm |
| Außendurchmesser | 135 mm |
| Dicke | 44 mm |
| Typ | SA |
| Gewicht | 5900 g |
| Gewinde | Linksgewinde |
| Schmierung | mit |
| Verpackung | 1 |

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE