

Winkelgelenke SA PM15-02-502-DURBAL - PM15-02-502-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/pm15-02-502-durbal>

PM15-02-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	weight	calculation factors	rotational speed limit	basic load rating	dyn. C	stat. C0
PM 15 -02	-502	15	M 20 x 1.5	18.5	42	26	20	14							
type		l1	l2	l3	h1	h2	u	z	alpha [°]	[kg]	Y	Y0	nmax [min-1]	C [N]	C0 [N]
PM 15	36	30	73.5	3.0	2.5	6.5	0.273			2.07	2.17	975	5485	3270	

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952507644
Innendurchmesser	15 mm
Außendurchmesser	42 mm
Dicke	20 mm
Typ	SA
Gewicht	273 g
Gewinde	Linksgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE