

Winkelgelenke SA

BRM16-60-501-DURBAL - BRM16-60-501-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brm16-60-501-durbal>

BRM16-60-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3402 D10k (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]									
type	sp/functional	int hard thread	d ₁	d ₂	d ₄	d ₅	b ₁	b ₂	h		
BRM 16 -60	-501		16	M 16	19,0	42	21	15,0	66		
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating			
type	l	l ₂	α [°]	[kg]	Y	v _c	Temp. [min.]	C [N]	C ₀ [N]		
BRM 16	40	22	8,0	0,190	2,24	2,35	975	4250	1600		

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952509167
Innendurchmesser	16 mm
Außendurchmesser	42 mm
Dicke	21 mm
Typ	-
Gewicht	190 g
Gewinde	-
Schmierung	-
Verpackung	-
Standard	-

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE