

Winkelgelenke SA BRM20-60-501-DURBAL - BRM20-60-501-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/sa/brm20-60-501-durbal>

BRM20-60-501



male thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished, rolled thread

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 2402 D1/L6 (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]							
type	sp/functional	lt/hard thread	d ₁	d ₂	d ₄	d ₅	b ₁	b ₂	h
BRM 20 -60	-501		20	M 20 x 1,5	24,5	50	25	18,0	78
measurements [mm]		weight	calculation-factors		rotational speed limit	basic load rating			
type	l	l ₂	α [°]	β [kg]	Y	v _c	C	d _{yn.}	stat. C ₀
BRM 20	47	28	7,0	0,338	2,46	2,58	825	5350	2300

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952509198
Innendurchmesser	20 mm
Innendurchmesser	0.787" inch
Außendurchmesser	50 mm
Außendurchmesser	1.969" inch
Dicke	25 mm
Dicke	0.984" inch
Typ	SA
Gewicht	338 g
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE