

Gelenkköpfe SI BRF16-60-501-DURBAL - BRF16-60-501-DURBAL

<https://www.123kugellager.ch/kugellager-gehauselager/gelenkkopfe-gelenklager/si/brf16-60-501-durbal>

BRF16-60-501



rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminum-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]												
type	light load thread	light load thread	light load thread											
type	l	l ₁	l ₂	SW	α [°]	weight	calculation-factors	rotational speed limit	basic load rating	stat.	stat.	stat.		
						[kg]	Y	v ₀	C	C ₁₀	C ₁₀	C ₁₀		
								max	[N]	[N]	[N]	[N]		
BRF 16 -60 -501	16	22,0	M 16	19,0	42	27	21	15,0	64					
BRF 16	28	8,0	22	22	8,0	0,224	2,24	2,35	975	4250	1600			

PRODUKTMERKMALE

Marke	DURBAL
N° Ean13	3663952509280
Innendurchmesser	16 mm
Innendurchmesser	0.63" inch
Außendurchmesser	42 mm
Außendurchmesser	1.654" inch
Dicke	21 mm
Dicke	0.827" inch
Typ	SI
Gewicht	224 g
Gewinde	Rechtsgewinde
Schmierung	mit
Verpackung	1
Standard	Ohne Standard

kontakt@123kugellager.ch

+49 (0) 800 001 076 6

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE